

IPC-HDW2431T-AS-S2-DG-028B -Turret fijo IP Dahua StarLight con Smart IR de 30 m para exterior



Precio: 142.5304€

SKU: IPC-HDW2431T-AS-S2-DG-028B

Link: <https://mundicam.atc.blue/productos/ofertas/videoip-ofertas/ipc-hdw2431t-as-s2-dg-028b/>

PRODUCT INFORMATION

Protección: 69

Alcance IR: 75

Lente: 60

Micrófono Integrado: 78

Resolución: 108

WDR: 64

WIFI: 65

Categorías: Cámaras IP Turret, Video-IP ?BLACK FRIDAY?, ? OFERTAS

Etiquetas: Black Friday, dahua

Domo fijo IP Dahua StarLight con Smart IR de 30 m para exterior CMOS 1/3" de 4MP Stream dual Formato H.265/H.264/MJPEG Resolución de hasta 4MP a 20ips Filtro ICR0,008 lux F1.6 Óptica fija de 2,8 mm (102°) OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, 4 zonas ROI, espejo, videosensor y mascarar de privacidad Detección inteligente (IVS) Incorpora micrófono Ranura MicroSD Onvif, CGI, P2PIP673 AXIS12V CCPE.

ESPECIFICACIONES TÉCNICAS

Cámara	
Sensor de imagen	CMOS progresivo de 1/3 "y 4 megapíxeles
Píxeles efectivos	2688 (H) × 1520 (V)
ROM	128 MB
RAM	128 MB
Sistema de escaneo	Progresivo
Velocidad de obturación electrónica	Auto / Manual 1/3 s – 1/100000 s

Min. Iluminación	0.008 Lux @ F1.6				
Distancia IR	30 m (98,43 pies)				
Control de encendido / apagado IR	Manual de auto				
Número de LED IR	2				
Pan / Tilt / Rango de rotación	Horizontal: 0 ° –360 ° Vertical: 0 ° –78 ° Rotación: 0 ° –360 °				
Lente					
Tipo de lente	Fijo				
Tipo de montaje	M12				
Longitud focal	2,8 mm				
Max. Abertura	F1.6				
Campo de visión	2.8 mm: horizontal: 102.0 ° vertical: 55.0 ° diagonal: 121.0 °				
Tipo de iris	Apertura fija				
Distancia de enfoque cercana	2,8 mm: 0,9 m (2,95 pies)				
DORI Distancia	Lente	Detectar	Observar	Reconocer	Identificar
	2,8 mm	56 m (183,73 pies)	22,4 m (73,49 pies)	11,2 m (36,75 pies)	5,6 m (18,37 pies)
Evento inteligente					
Análisis general de IVS	Intrusión; cable trampa				
Vídeo					
Compresión de video	H.265; H.264; H.264B; MJPEG				
Códec inteligente	si				
Velocidad de fotogramas de vídeo	Convencional:				
	2688 × 1520 (1 fps-20 fps)				
	2560 × 1440 (1 fps-25/30 fps)				
	Sub corriente:				
	704 × 576 (1 fps-25 fps)				
	704 × 480 (1 fps-30 fps)				
Capacidad de transmisión	2 streams				
Resolution	2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)				
Bit Rate Control	CBR/VBR				
Video Bit Rate	H.264: 32 Kbps–6144 Kbps H.265: 12 Kbps–6144 Kbps				
Day/Night	Auto(ICR)/Color/B/W				
BLC	Yes				
HLC	Yes				
WDR	120 dB				
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest(Roi)	Yes (4 areas)				
Smart IR	Yes				
Image Rotation	0°/90°/180°/270° (Supports 90°/270° with 1080p resolution.)				
Mirror	Yes				
Privacy Masking	4 areas				
Audio					

Built-in MIC	Yes
Audio Compression	G.711A; G.711Mu; G.726; AAC
Network	
Network	RJ-45 (10/100 Base-T)
Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; 802.1x; Bonjour
Interoperability	ONVIF(Profile S/Profile G);CGI;P2P;Milestone;Genetec
User/Host	20
Edge Storage	Cloud; FTP; SFTP; Micro SD Card (support max. 256 GB); NAS
Browser	IE Chrome Firefox
Management Software	Smart PSS; DSS; DMSS
Mobile Phone	IOS; Android
Certification	
Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
Power	
Power Supply	12V DC/PoE (802.3af)
Power Consumption	< 6.6W
Environment	
Operating Conditions	-40°C to +60°C (-40°F to +140°F)/less than ? 95%
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Protection	IP67
Structure	
Casing	Metal + Plastic
Dimensions	100.9 mm × ?109.9 mm (3.97" × ?4.33")
Net Weight	0.39 kg (0.9 lb)
Gross Weight	0.56 kg (1.2 lb)